



## Cylinder 279 CORD H: 9 W: 6 OAL: 45.75

### Description

6" diameter cylinder, suspended by 36" Black 18-3 cord  
 (White cord supplied with white fixtures)  
 Designed for use with uni-directional LED or reflector type (R/PAR) lamps

### Specifications

<b>Housing</b>	Spun aluminum cylinder with stamped steel canopy	
<b>Diffuser/Optics</b>	Bare lamp (open aperture)	
<b>Light Source</b>	MBL	Medium Base
<b>Max Watts</b>	25	120
<b>Electrical</b>	MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures. MBL - Includes Medium base 120V HPF Triac dimmable LED PAR lamp rated for use in fully enclosed fixtures.	
<b>Mounting</b>	Mounts over 4" recessed outlet box.	
<b>Certification</b>	Manufactured in accordance with U.L. standard 1598 - For dry locations only	



### Ordering Guide: Choose from each category, using designated code to specify.

279 CORD					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

#### Diffuser/Optics

- Bare-lamp (open aperture)

#### Light Source

**MBL15 PAR FL** - 15W/30K 1200 Lm PAR38  
**MBL15 PAR SP** - 15W/30K 1200 Lm PAR38  
**MBL15 PAR WFL** - 15W/30K 1200 Lm PAR38  
**MBL18 PAR FL** - 18W/30K 1400 Lm PAR38  
**MB25 PAR** - 25W MAX. MED base (Par38 lamp by others)  
**MB** - Maximum 120W Par38 (by others)

#### Finish

**Standard**  
**BL** - Black  
**DB** - Dura-Bronze  
**WH** - White  
**Upgraded\***  
**RAL** - Specify Color #  
**UPG** - Select Color from Luraline Palette  
**Premium\***  
**CCM** - Custom Color  
**CIC** - Inner Color  
**CTC** - Clear Top Coat  
 \* Subject to Surcharge

#### Extras (Order Separately)

**B79** Black milli-groove baffle (Not Available with Tempered glass lens)  
**SSP 120** 4KV 120V MOV1 Surge Suppressor