



**Cylinder 279 UD** H: 16.75 W: 6 E: 8.50 MC: 8.38

**Description**

6" Diameter Up/Down cylinder wall-mount  
Designed for use with uni-directional LED or reflector type (R/PAR) lamps

**Specifications**

**Housing** Extruded aluminum cylinder with die-cast arm/back

**Diffuser/Optics** Bare lamp (open aperture)

**Light Source** MBL Medium Base

**Max Watts** 25 X 2 120 X 2

**Electrical**  
**MB** - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.  
**MBL** - Includes Medium base 120V HPF Triac dimmable LED PAR lamp rated for use in fully enclosed fixtures.  
**GUL** - Includes GU24 base 120V HPF Triac dimmable 25,000 Hr OmniLED A lamp with integrated driver.

**Mounting** Mounts over 4" recessed outlet box.

**Certification** Manufactured in accordance with U.L. standard 1598 - For dry locations only



**Ordering Guide:** Choose from each category, using designated code to specify.

279 UD				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

**Diffuser/Optics**  
- Bare-lamp (open aperture)

**Light Source**  
**2MBL15 PAR FL** - 30W/30K 2400 Lm PAR38  
**2MBL15 PAR SP** - 30W/30K 2400 Lm PAR38  
**2MBL15 PAR WFL** - 30W/30K 2400 Lm PAR38  
**2MBL18 PAR FL** - 36W/30K 2800 Lm PAR38  
**2MB25 PAR** - 2x 25W MAX. MED base (lamp by others)  
**MB** - Maximum 2x120W Par38 (by others)

**Finish**  
**Standard**  
**WH** - White  
**Upgraded\***  
**RAL** - Specify Color #  
**UPG** - Select Color from [Luraline Palette](#)  
**Premium\***  
**CCM** - Custom Color  
**CIC** - Inner Color  
**CTC** - Clear Top Coat  
 \* Subject to Surcharge

**Extras (Order Separately)**