



Cylinder 279 WM R H: 9 W: 6 E: 8.50 MC: 2.50

Description

6" Diameter Downlight cylinder wall-mount w/Reflector
Designed for use with uni-directional LED or non-reflector type lamps

Specifications

Housing Spun aluminum cylinder with die-cast arm/back

Diffuser/Optics Bare lamp (open aperture)

Light Source MBL Medium Base

Max Watts 10 60

Electrical
MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.
MBL - Includes Medium base 120V HPF Triac dimmable LED PAR lamp rated for use in fully enclosed fixtures.
GUL - Includes GU24 base 120V HPF Triac dimmable 25,000 Hr OmniLED A lamp with integrated driver.
DOB - Includes 120V HPF Triac dimmable 50,000 Hr LED light engine with Driver on Board.

Mounting Mounts over 4" recessed outlet box.

Certification Manufactured in accordance with U.L. standard 1598 - For dry locations only

Ordering Guide: Choose from each category, using designated code to specify.



Diffuser/Optics

- Bare-lamp (open aperture)

Light Source

MBL9.8A - 9.8W/30K 800 Lm OmniLED
MBL10A JAB - 10W/30K 800 Lm 90+ CRI OmniLED
MB - Maximum 60W A (by others)

Finish

Standard
DB - Dura-Bronze
Upgraded*
RAL - Specify Color #
UPG - Select Color from Luraline Palette
Premium*
CCM - Custom Color
CIC - Inner Color
CTC - Clear Top Coat
 * Subject to Surcharge

Extras (Order Separately)