



## Cylinder 288 CMR H: 12.88 W: 8

### Description

8" Square, surface-mounted cylinder w/Reflector  
Designed for use with LED light engines or non-reflector type lamps

### Specifications

**Housing** Extruded aluminum cylinder with extended canopy (not shown)

**Diffuser/Optics** Bare lamp (open aperture)

<b>Light Source</b>	GUL	MBL	Medium Base
<b>Max Watts</b>	15	11	150

**Electrical**

- MB** - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.
- MBL** - Includes Medium base 120V HPF Triac dimmable LED PAR lamp rated for use in fully enclosed fixtures.
- GUL** - Includes GU24 base 120V HPF Triac dimmable 25,000 Hr OmniLED A lamp with integrated driver.

**Mounting** Mounts over 4" recessed outlet box.

**Certification** Manufactured in accordance with U.L. standard 1598 -



### Ordering Guide: Choose from each category, using designated code to specify.



#### Diffuser/Optics

- Bare-lamp (open aperture)

#### Light Source

**GUL11A** - 11W/27K 1100 Lm GU24 OmniLED  
**MBL11A** - 11W/30K 1100 Lm OmniLED  
**MBL11A** - 11W/30K 1100 Lm OmniLED  
**GUL15A** - 15W/27K 1600 Lm GU24 OmniLED  
**MB** - 150W Max Incand A (by others)

#### Finish

**Standard**  
**WH** - White  
**Upgraded\***  
**RAL** - Specify Color #  
**UPG** - Select Color from Luraline Palette  
**Premium\***  
**CCM** - Custom Color  
**CIC** - Inner Color  
**CTC** - Clear Top Coat  
 \* Subject to Surcharge

#### Extras (Order Separately)