



## Wall Pack/Floodlight AWP15 H: 9 W: 14.25 E: 7.25

### Description

Medium Wall Pack

### Specifications

**Housing** Die-cast aluminum w/Hinged front frame

**Diffuser/Optics** Prismatic Borosilicate glass

**Light Source** LTE

**Max Watts** 42

**Electrical** LTE - Includes 50,000 Hr. LED light engine with 120-277V constant current driver.  
 QE/TE - Includes 4-pin CF lamp with 120-277V HPF electronic ballast

**Mounting** Mounts over 4" recessed outlet box or via surface conduit

**Certification**



**Ordering Guide:** Choose from each category, using designated code to specify.

AWP15				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

#### Diffuser/Optics

Clear Prismatic Borosilicate glass

#### Light Source

**L42 LTE 50K** - 41.5W/50K 5788 lumen LED

#### Finish

**Standard**  
**ZT** - Bronze

#### Extras (Order Separately)

**(D) FUSE** DOUBLE FUSED  
**(S) FUSE** SINGLE FUSED  
**BBE** Battery Backup - For Compact Fluorescent only (specify 120V Or 277V)  
**BBL** 90 minutes Battery Backup - For LED only (100- 277V/50-60Hz Input Voltage)  
**PC1** Field installed 120V PHOTOCELL  
**SSP** 10KV 120-277V Supplemental Surge Protection