



Wall Pack/Floodlight AWP35 H: 9-1/8 W: 18 E: 7-1/8

Description

Half Round Cut Off Wall Sconce Downlight, Type III distribution

Specifications

Housing Die-cast aluminum

Diffuser/Optics Clear Tempered Glass

Light Source LTE

Max Watts 47

Electrical LTE - Includes 50,000 Hr. LED light engine with 120-277V constant current driver.
QE/TE - Includes 4-pin CF lamp with 120-277V HPF electronic ballast

Mounting Mounts over 4" recessed outlet box

Certification



Ordering Guide: Choose from each category, using designated code to specify.

AWP35					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

Diffuser/Optics

Clear Tempered Glass lens

Light Source

L47 LTE 50K - 46.5W/50K 5445 lumen LED

Finish

Standard
BT - Black (textured)
ZT - Bronze (textured)

Extras (Order Separately)

(D) FUSE DOUBLE FUSED
(S) FUSE SINGLE FUSED
BBL 90 minutes Battery Backup - For LED only (100- 277V/50-60Hz Input Voltage)
PC1 Field installed 120V PHOTOCELL
PC2 Field installed 277V PHOTOCELL
SSP 10KV 120-277V Supplemental Surge Protection