



Wall Pack/Floodlight AWP15 H: 12 W: 11.13 E: 7.88

Description

Curved die cast Wall Pack supplied with fully gasketted borosilicate glass diffuser and anodized aluminum reflector

Specifications

- Housing** Die-cast aluminum w/hinged front frame
- Diffuser/Optics** Clear Prismatic Borosilicate glass
- Light Source** LTE
- Max Watts** 37.2
- Electrical** LTE - Includes 50,000 Hr. LED light engine with 120-277V constant current driver.
QE/TE - Includes 4-pin CF lamp with 120-277V HPF electronic ballast
- Mounting** Mounts over 4" recessed outlet box or surface conduit
- Certification**



Ordering Guide: Choose from each category, using designated code to specify.

AWPA15				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

Clear Prismatic glass

Light Source

L37 LTE 50K - 37.2W/50K 5045 lumen LED

Finish

Standard
ZT - Bronze

Extras (Order Separately)

- (D) FUSE** DOUBLE FUSED
- (S) FUSE** SINGLE FUSED
- BBE** Battery Backup - For Compact Fluorescent only (specify 120V Or 277V)
- BBL** 90 minutes Battery Backup - For LED only (100- 277V/50-60Hz Input Voltage)
- SSP** 10KV 120-277V Supplemental Surge Protection