



Wall Pack/Floodlight AWPB40

H: 12.25 W: 10.38 E: 9.38

Description

Euro styled Polycarbonate Hooded Wall Pack supplied with fully gasketted clear prismatic polycarbonate diffuser and anodized aluminum reflector

Specifications

Housing Die-cast aluminum with polycarbonate front

Diffuser/Optics Clear Ribbed Polycarbonate

Light Source Fluorescent LTE Fluorescent

Max Watts 42 33.5 42 X 2

Electrical LTE - Includes 50,000 Hr. LED light engine with 120-277V constant current driver.
QE/TE - Includes 4-pin CF lamp with 120-277V HPF electronic ballast

Mounting Mounts over 4" recessed outlet box or surface conduit

Certification



Ordering Guide: Choose from each category, using designated code to specify.

AWPB40				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

Ribbed Polycarbonate

Light Source

- F26 TE - 26W/30K 1800 lumen CF
- 2F26 TE - 52W/30K 3600 lumen CF
- F32 TE - 32W/30K 2400 lumen CF
- 2F32 TE - 64W/30K 4800 lumen CF
- L34 LTE 50K - 33.5W/50K 4438 lumen LED
- 2F42 TE - 84W/30K 6400 lumen CF
- F42 TE - 42W/30K 3200 lumen CF

Finish

- Standard
- ZT - Bronze

Extras (Order Separately)

- (D) FUSE DOUBLE FUSED
- (S) FUSE SINGLE FUSED
- BBE Battery Backup - For Compact Fluorescent only (specify 120V Or 277V)
- SSP 10KV 120-277V Supplemental Surge Protection