



**Wall Pack/Floodlight FH15 BR** H: 3.63 W: 9.5 E: 15.5

**Description**

This sturdy area light is ideal for applications requiring a sleek, stylish design combined with a high-output, energy-efficient light source. Made with a die cast aluminum housing and coated with a textured bronze powdercoat finish, this fixture is ideal for high visibility areas. Delivers more than 3,100 lumens, while consuming only 21.7 watts. CSA listed for wet locations. Optional surge protection and photocell. Available with tempered clear flat glass lens or optional LED flat glass lens. Comes with a choice of 3 different mounting options - arm, two-piece swivel bracket or adjustable slip fitter.

**Specifications**

**Diffuser/Optics**

- Clear Glass (Type III)
- Clear Glass (Type V)

**Light Source** LTE

**Max Watts** 37.2

**Electrical** LTE - Includes 50,000 Hr. LED light engine with 120-277V constant current driver.

**Mounting** Mounts via heavy duty stationary arm

**Certification**



**Ordering Guide:** Choose from each category, using designated code to specify.

FH15 BR				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

**Diffuser/Optics**

**C3** - Clear Glass (Type III)  
**C5** - Clear Glass (Type V)

**Light Source**

**L21.7 LTE 50K** - 21.7W/50K 3140 delivered lumens  
**L37.2 LTE 50K** - 37.2W/50K 4100 delivered lumens

**Finish**

**Standard**  
**ZT** - Bronze

**Extras (Order Separately)**

**(D) FUSE** DOUBLE FUSED  
**(S) FUSE** SINGLE FUSED  
**40K**  
**GS180** 180° Glare Shield