



Wall Pack/Floodlight FH15 SF H: 3.63 W: 9.5 E: 18.75

Description

This sturdy area light is ideal for applications requiring a sleek, stylish design combined with a high-output, energy-efficient light source. Made with a die cast aluminum housing and coated with a textured bronze powdercoat finish, this fixture is ideal for high visibility areas. Delivers more than 3,100 lumens, while consuming only 21.7 watts. CSA listed for wet locations. Optional surge protection and photocell. Available with tempered clear flat glass lens or optional LED flat glass lens Comes with a choice of 3 different mounting options - arm, two-piece swivel bracket or adjustable slip fitter.

Specifications

Diffuser/Optics

- Clear Glass (Type III)
- Clear Glass (Type V)

Light Source LTE

Max Watts 37.2

Electrical LTE - Includes 50,000 Hr. LED light engine with 120-277V constant current driver.

Mounting Mounts via heavy duty stationary arm

Certification



Ordering Guide: Choose from each category, using designated code to specify.

FH15 SF					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

Diffuser/Optics

C3 - Clear Glass (Type III)
C5 - Clear Glass (Type V)

Light Source

L21.7 LTE 50K - 21.7W/50K 3140 delivered lumens
L37.2 LTE 50K - 37.2W/50K 4100 delivered lumens

Finish

Standard
ZT - Bronze

Extras (Order Separately)

(D) FUSE DOUBLE FUSED
(S) FUSE SINGLE FUSED
40K
GS180 180° Glare Shield