



Helos HL302 UWM H: 19 W: 14 E: 21.75 MC: 14.25

Description

14" Tapered, U-arm

Specifications

| | | | |
|------------------------|---|-----|-------------|
| Housing | Heavy-wall spun aluminum with cast fitter/canopy and extruded arm | | |
| Diffuser/Optics | <ul style="list-style-type: none"> • Clear tempered glass cylinder • Frosted glass cylinder | | |
| Light Source | GUL | MBL | Medium Base |
| Max Watts | 11 | 13 | 100 |
| Electrical | MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures. MBL - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures. GUL - Includes GU24 base 120V HPF Triac dimmable 25,000 Hr OmniLED A lamp with integrated driver. | | |
| Mounting | Mounts over 4" recessed outlet box. | | |
| Certification | Manufactured in accordance with U.L. standard 1598 Suitable for damp or dry locations - Suitable for wet locations | | |



Ordering Guide: Choose from each category, using designated code to specify.

| | | | | |
|-----------|----------|--------------|--------|--------|
| HL302 UWM | | | | |
| MODEL | DIFFUSER | LIGHT SOURCE | FINISH | EXTRAS |

Diffuser/Optics

- CL - Clear glass
- FR - Frosted glass

Light Source

- MB25 A** - 25W MAX. MED base (A19 lamp by others)
- MBL6A** - 5.5W/30K 470 Lm OmniLED
- MBL9.8A** - 9.8W/30K 800 Lm OmniLED
- GUL9.8A** - 9.8W/27K 800 Lm GU24 OmniLED
- MBL10A JAB** - 10W/30K 800 Lm 90+ CRI OmniLED
- MBL11A** - 11W/30K 1100 Lm OmniLED
- GUL11A** - 11W/27K 1100 Lm GU24 OmniLED
- MBL13A JAB** - 13W/30K 1100 Lm 90+ CRI OmniLED
- MB** - 100W Max Incand A (by others)

Finish

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded***
- RAL** - Specify Color #
- UPG** - Select Color from Luraline Palette
- Premium***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)