



## Wall Pack/Floodlight L100 H: 12.2" W: 9" E: 10.5"

### Description

Wall Mount LED Lantern

### Specifications

Housing	Injection-molded polypropylene	
Diffuser/Optics	Frosted Acrylic Lens	
Light Source	DOB	Medium Base
Max Watts	13	60
Electrical	<b>MB</b> - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures. <b>DOB</b> - Includes 120V HPF Triac dimmable 50,000 Hr LED light engine with Driver on Board.	
Mounting	Mounts over 4" recessed outlet box.	
Certification	Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations	



**Ordering Guide:** Choose from each category, using designated code to specify.

LH100					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

#### Diffuser/Optics

F - Frosted Acrylic Lens

#### Light Source

**L13 DOB** - 13W/30K 1140 lumen LED  
**MB** - Maximum 60W A (by others)

#### Finish

**Standard**  
**B** - Black  
**W** - White  
**Z** - Bronze (94)

#### Extras (Order Separately)

**40K**  
**PC1** Field installed 120V PHOTOCELL