



Wall Pack/Floodlight LH103 H: 15.25" W: 7.4" E: 9" MC: 2.75"

Description

Wall Mount LED Lantern

Specifications

| | | |
|------------------------|---|-------------|
| Housing | Injection-molded polypropylene | |
| Diffuser/Optics | Frosted Acrylic Lens | |
| Light Source | DOB | Medium Base |
| Max Watts | 13 | 60 |
| Electrical | MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures. DOB - Includes 120V HPF Triac dimmable 50,000 Hr LED light engine with Driver on Board. | |
| Mounting | Mounts over 4" recessed outlet box. | |
| Certification | Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations | |



Ordering Guide: Choose from each category, using designated code to specify.

| | | | | | |
|-------|----------|--------------|--------|--------|--|
| LH103 | | | | | |
| MODEL | DIFFUSER | LIGHT SOURCE | FINISH | EXTRAS | |

Diffuser/Optics

F - Frosted Acrylic Lens

Light Source

L13 DOB - 13W/30K 1140 lumen LED
MB - Maximum 60W A (by others)

Finish

Standard
B - Black
W - White
Z - Bronze (94)

Extras (Order Separately)

40K
PC1 Field installed 120V PHOTOCELL