



**Wall Pack/Floodlight LH145** H: 11.6" W: 4.75" E: 6.8" MC: 2.25"

**Description**

Wall Mount LED Lantern

**Specifications**

<b>Housing</b>	Injection-molded polypropylene	
<b>Diffuser/Optics</b>	Frosted Acrylic Lens	
<b>Light Source</b>	DOB	Medium Base
<b>Max Watts</b>	13	60
<b>Electrical</b>	<b>MB</b> - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures. <b>DOB</b> - Includes 120V HPF Triac dimmable 50,000 Hr LED light engine with Driver on Board.	
<b>Mounting</b>	Mounts over 4" recessed outlet box.	
<b>Certification</b>	Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations	



**Ordering Guide:** Choose from each category, using designated code to specify.

LH145					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

**Diffuser/Optics**

F - Frosted Acrylic Lens

**Light Source**

**L13 DOB** - 13W/30K 1140 lumen LED  
**MB** - Maximum 60W A (by others)

**Finish**

**Standard**  
**B** - Black  
**W** - White  
**Z** - Bronze (94)

**Extras (Order Separately)**

**40K**  
**PC1** Field installed 120V PHOTOCELL