



**Area/Bollard LBOSFRL** H: 41.38 W: 7

### Description

This is a square-shaped bollard with a flat-top design and cone reflector. It is very popular in public parks and walkways because it is both affordable and durable. The extruded aluminum housing with flush-mounting base and vandal-resistant screws, black powdercoat finish over chromate conversion coating, internal ballast tray, and 50,000 estimated life makes this fixture very easy to maintain. The LED light source delivers up to 2,089 lumens while using just 14.5 watts. Standard with electronic 120/277 dimmable driver. CSA listed for wet locations.

### Specifications

- Housing** Extruded aluminum with cast base
- Diffuser/Optics** Clear Polycarbonate
- Light Source** LTE
- Max Watts** 14.5
- Electrical** LTE - Includes 50,000 Hr. LED light engine with 120-277V constant current driver.
- Mounting** Mounting kit with 8" anchor bolts included
- Certification** Manufactured in accordance with U.L. standard 1598 - CSA Listed for Wet Locations



**Ordering Guide:** Choose from each category, using designated code to specify.

LBOSFRL				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

#### Diffuser/Optics

Clear Polycarbonate Lens

#### Light Source

**L15 LTE 50K** - 14.5W/50K 2089 lumen LED

#### Finish

**Standard**  
**BT** - Black (textured)  
**ZT** - Bronze

#### Extras (Order Separately)

**(D) FUSE** DOUBLE FUSED  
**(S) FUSE** SINGLE FUSED  
**BBL** 90 minutes Battery Backup - For LED only (100- 277V/50-60Hz Input Voltage)  
**SSP** 10KV 120-277V Supplemental Surge Protection