



Cylinder 260 UDX H: 12.88 W: 4.50 E: 9 MC: 7

Description

4.5" Square Up/Down cylinder wall-mount
Designed for use with LED light engines

Specifications

Housing	Extruded aluminum cylinder with die-cast arm/back*
Diffuser/Optics	Bare Lamp (no diffuser)
Light Source	LED
Max Watts	6.32 X 2
Electrical	TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
Mounting	Mounts over 4" recessed outlet box.
Certification	Manufactured in accordance with U.L. standard 1598 - For dry locations only

Ordering Guide: Choose from each category, using designated code to specify.

260 UDX				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

Bare-lamp - no diffuser

Light Source

2TL3 HO - 6.08W/40K 1964 Lm, 0-10V dimmable
2TL3 - 3.11W/30K 603 Lm, 0-10V dimmable
2TL5 HO - 9.2W/40K 2408 Lm, 120V dimmable
2TL5 - 9.4W/30K 1708 Lm, 120V dimmable
2TL6 HO - 12.32W/40K 3176 Lm, 120V dimmable
2TL6 - 12.64W/30K 2416 Lm, 120V dimmable

Finish

Standard
BL - Black
DB - Dura-Bronze
WH - White
Upgraded*
RAL - Specify Color #
UPG - Select Color from Luraline Palette
Premium*
CCM - Custom Color
CIC - Inner Color
CTC - Clear Top Coat
 * Subject to Surcharge

Extras (Order Separately)

27K Non-Stock item - consult factory for availability
2DIM010 LED 4-wire 0-10V Dimming - 120-277V
35K Neutral White
SSP 10KV 120-277V Supplemental Surge Protection

NOTES:

*Driver is housed in extended aluminum canopy (not shown)