



Cylinder 279 UD H: 16.75 W: 6 E: 8.50 MC: 8.38

Description

6" Diameter Up/Down cylinder wall-mount
Designed for use with uni-directional LED or reflector type (R/PAR) lamps

Specifications

- Housing** Extruded aluminum cylinder with die-cast arm/back
- Diffuser/Optics** Bare lamp (open aperture)
- Light Source** MBL Medium Base
- Max Watts** 25 X 2 120 X 2
- Electrical** MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.
MBL - Includes Medium base 120V HPF Triac dimmable LED PAR lamp rated for use in fully enclosed fixtures.
- Mounting** Mounts over 4" recessed outlet box.
- Certification** Manufactured in accordance with U.L. standard 1598 - For dry locations only



Ordering Guide: Choose from each category, using designated code to specify.

| | | | | |
|--------|----------|--------------|--------|--------|
| 279 UD | | | | |
| MODEL | DIFFUSER | LIGHT SOURCE | FINISH | EXTRAS |

Diffuser/Optics

- Bare-lamp (open aperture)

Light Source

- 2MBL15 PAR FL** - 30W/30K 2400 Lm PAR38
- 2MBL15 PAR SP** - 30W/30K 2400 Lm PAR38
- 2MBL15 PAR WFL** - 30W/30K 2400 Lm PAR38
- 2MBL18 PAR FL** - 36W/30K 2800 Lm PAR38
- 2MB25 PAR** - 2x 25W MAX. MED base (lamp by others)
- MB** - Maximum 2x120W Par38 (by others)

Finish

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded***
- RAL** - Specify Color #
- UPG** - Select Color from Luraline Palette
- Premium***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- * Subject to Surcharge

Extras (Order Separately)