



Decorative 714 CORDX H: 14 W: 14 OAL: 52.50

Description

14" Globe pendant with 36" Black 18-3 cord. (White cord supplied with white fixtures)

Specifications

Housing	Stamped steel fitter and canopy*
Diffuser/Optics	WACS - Seamless White Acrylic
Light Source	LED
Max Watts	14.69
Mounting	Mounts over 4" recessed outlet box.
Certification	Manufactured in accordance with U.L. standard 1598 - For dry locations only

Ordering Guide: Choose from each category, using designated code to specify.

714 CORDX				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

WACS - 1-piece White Acrylic (blow-molded)

Light Source

TL6 HO - 6.16W/40K 1588 Lm, 120V dimmable
TL6 - 6.32W/30K 1208 Lm, 120V dimmable
TL8 HO - 7.75W/40K 1886 Lm, 120V dimmable
TL8 - 7.96W/30K 1502 Lm, 120V dimmable
TL9 HO - 9.36W/40K 2179 Lm, 120V dimmable
TL10 - 9.62W/30K 1790 Lm, 120V dimmable
TL11 HO - 10.99W/40K 2470 Lm, 120V dimmable
TL11 - 11.3W/30K 2075 Lm, 120V dimmable
TL13 - 12.99W/30K 2352 Lm, 120V dimmable
TL14 HO - 14.28W/40K 3040 Lm, 120V dimmable
TL15 - 14.69W/30K 2626 Lm, 120V dimmable

Finish

Standard
WH - White
Upgraded*
RAL - Specify Color #
UPG - Select Color from Luraline Palette
Premium*
CCM - Custom Color
CIC - Inner Color
CTC - Clear Top Coat
 * Subject to Surcharge

Extras (Order Separately)

27K Non-Stock item - consult factory for availability
35K Neutral White
50K Daylight (Non-Stock item - consult factory for availability)
DIM010 4-wire 0-10V Dimming - 120-277V (STANDARD on TL19 & higher)
SSP 10KV 120-277V Supplemental Surge Protection

NOTES:

*Driver is housed in extended aluminum canopy (not shown)