



Decorative CP12 STEMX H: 13.50 W: 12.50 OAL: 29

Description

Prismatic reflector pendant with 12" stem and 40° swivel canopy

Specifications

Housing	Spun aluminum bullet with stamped steel canopy*
Diffuser/Optics	Lensed LED (no diffuser) for Dry locations only
Light Source	LED
Max Watts	16.41
Electrical	TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
Mounting	Mounts over 4" recessed outlet box.
Certification	Manufactured in accordance with U.L. standard 1598 - For dry locations only

Ordering Guide: Choose from each category, using designated code to specify.

CP12 STEMX				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

- Lensed LED (no diffuser)

Light Source

TL3 HO - 3.04W/40K 982 Lm, 0-10V dimmable
TL3 - 3.11W/30K 603 Lm, 0-10V dimmable
TL5 HO - 4.59W/40K 1287 Lm, 120V dimmable
TL5 - 4.7W/30K 909 Lm, 120V dimmable
TL6 - 6.32W/30K 1208 Lm, 120V dimmable
TL8 HO - 7.75W/40K 1886 Lm, 120V dimmable
TL8 - 7.96W/30K 1502 Lm, 120V dimmable
TL9 HO - 9.36W/40K 2179 Lm, 120V dimmable
TL10 - 9.62W/30K 1790 Lm, 120V dimmable
TL11 - 11.3W/30K 2075 Lm, 120V dimmable
TL13 HO - 12.62W/40K 2756 Lm, 120V dimmable
TL13 - 12.99W/30K 2352 Lm, 120V dimmable
TL16 - 16.41W/30K 2895 Lm, 120V dimmable

Finish

Standard
BL - Black
DB - Dura-Bronze
WH - White
Upgraded*
RAL - Specify Color #
UPG - Select Color from Luraline Palette
Premium*
CCM - Custom Color
CIC - Inner Color
CTC - Clear Top Coat
 * Subject to Surcharge

Extras (Order Separately)

27K Non-Stock item - consult factory for availability
35K Neutral White
DIM010 4-wire 0-10V Dimming - 120-277V (STANDARD on TL19 & higher)
DWG12 12" Drop Wire Guard
SSP 10KV 120-277V Supplemental Surge Protection

NOTES:

*Driver is housed in extended aluminum canopy (not shown)