



Decorative CP16 STEM H: 18.75 W: 16.38 OAL: 32.5

Description

Prismatic reflexor pendant with 12" stem and 40° swivel canopy

Specifications

Housing Spun aluminum bullet with stamped steel canopy

Diffuser/Optics Bare lamp (no diffuser) for Dry locations only

Light Source GUL MBL Medium Base

Max Watts 15 18 75

Electrical

- MB** - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.
- MBL** - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures.
- GUL** - Includes GU24 base 120V HPF Triac dimmable 25,000 Hr OmniLED A lamp with integrated driver.

Mounting Mounts over 4" recessed outlet box.

Certification Manufactured in accordance with U.L. standard 1598 - For dry locations only



Ordering Guide: Choose from each category, using designated code to specify.

CP16 STEM				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser / Optics

Bare-lamp (no diffuser)

Light Source

MB25 A - 25W MAX. MED base (A19 lamp by others)
MBL9.8A - 9.8W/30K 800 Lm OmniLED
MBL10A JA8 - 10W/30K 800 Lm 90+ CRI OmniLED
MBL11A - 11W/30K 1100 Lm OmniLED
GUL15A - 15W/27K 1600 Lm GU24 OmniLED
MBL15A - 15./30K 1600 Lm OmniLED
MBL18A JA8 - 18W/30K 1600 Lm 90+ CRI OmniLED
MB - Maximum 75W A (by others)

Finish

Standard
BL - Black
DB - Dura-Bronze
WH - White
Upgraded*
RAL - Specify Color #
UPG - Select Color from
[Luraline Palette](#)
Premium*
CCM - Custom Color
CIC - Inner Color
CTC - Clear Top Coat
 * Subject to Surcharge

Extras (Order Separately)

DWG16 16" Wire Guard
SSP 120 4KV 120V MOV1
 Surge Suppressor

NOTES: DWG Wire Guard may NOT be used in combination with CDL diffuser.
 DWG Wire Guard may NOT be used in combination with CDL diffuser.
 DWG Wire Guard may NOT be used in combination with CDL diffuser.
 DWG Wire Guard may NOT be used in combination with CDL diffuser.