



Decorative CP16 STEMX H: 18.75 W: 16.38 OAL: 34.25

Description

Prismatic reflexor pendant with 12" stem and 40° swivel canopy

Specifications

Housing	Spun aluminum bullet with stamped steel canopy
Diffuser/Optics	Lensed LED (no diffuser) for Dry locations only
Light Source	LED
Max Watts	26.98
Electrical	TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
Mounting	Mounts over 4" recessed outlet box.
Certification	Manufactured in accordance with U.L. standard 1598 - For dry locations only



Ordering Guide: Choose from each category, using designated code to specify.

CP16 STEMX				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

LOZ - Lensed LED (no diffuser)

Light Source

TL3 HO - 3.04W/40K 982 Lm, 0-10V dimmable
TL9 HO - 9.36W/40K 2179 Lm, 120V dimmable
TL11 - 11.3W/30K 2075 Lm, 120V dimmable
TL13 - 12.99W/30K 2352 Lm, 120V dimmable
TL14 HO - 14.28W/40K 3040 Lm, 120V dimmable
TL15 - 14.69W/30K 2626 Lm, 120V dimmable
TL16 HO - 15.94W/40K 3320 Lm, 120V dimmable
TL16 - 16.41W/30K 2895 Lm, 120V dimmable
TL20 - 19.9W/30K 3421 Lm, 0-10V dimmable
TL23 - 23.41W/30K 3931 Lm, 0-10V dimmable
TL26 HO - 26.16W/40K 4938 Lm, 0-10V dimmable
TL27 - 26.98W/30K 4428 Lm, 0-10V dimmable

Finish

Standard
BL - Black
DB - Dura-Bronze
WH - White
Upgraded*
RAL - Specify Color #
UPG - Select Color from Luraline Palette
Premium*
CCM - Custom Color
CIC - Inner Color
CTC - Clear Top Coat
 * Subject to Surcharge

Extras (Order Separately)

27K Non-Stock item - consult factory for availability
35K Neutral White
DIM010 4-wire 0-10V Dimming - 120-277V (STANDARD on TL19 & higher)
DWG16 16" Wire Guard
SSP 10KV 120-277V Supplemental Surge Protection

NOTES: *Driver is housed in extended aluminum canopy (not shown)
 *Driver is housed in extended aluminum canopy (not shown)
 *Driver is housed in extended aluminum canopy (not shown)
 *Driver is housed in extended aluminum canopy (not shown)