



RLM CS16 STEMX H: 10.38 W: 16.25 OAL: 24.125

Description

16" RLM pendant with 12" stem and 40° swivel canopy

Specifications

Housing	Spun aluminum shade with stamped steel canopy*
Diffuser/Optics	Lensed LED (no diffuser) for Dry locations only
Electrical	TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
Mounting	Mounts over 4" recessed outlet box.
Certification	Manufactured in accordance with U.L. standard 1598 - For dry locations only

Ordering Guide: Choose from each category, using designated code to specify.

<u>CS16 STEMX</u>	<u> </u>	<u> </u>	<u> </u>	<u> </u>
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

- Lensed LED (no diffuser)

Light Source

Finish

Standard

BL - Black
DB - Dura-Bronze
WH - White
Upgraded*
RAL - Specify Color #
UPG - Select Color from Luraline Palette

Premium*

CCM - Custom Color
CIC - Inner Color
CTC - Clear Top Coat
 * Subject to Surcharge

Extras (Order Separately)

27K Non-Stock item - consult factory for availability
35K Neutral White
DIM010 4-wire 0-10V Dimming - 120-277V (STANDARD on TL19 & higher)
DWG16 16" Wire Guard
SSP 10KV 120-277V Supplemental Surge Protection

NOTES:

*Driver is housed in extended aluminum canopy (not shown)