


Project:

Fixture Type:





**HL301 WM** Helos H: 10.5 W: 10 E: 17 MC: 3

## Description

10" Disk, Arm-mount

# **Specifications**

Housing Heavy-wall spun aluminum with cast fitter/canopy and extruded arm

Diffuser/Optics • Clear tempered glass cylinder

· Frosted Glass cylinder

**Light Source GUL MBL** Medium Base

Max Watts 11 13 100

Electrical MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.

MBL - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures.

- Includes GU24 base 120V HPF Triac dimmable 25,000 Hr OmniLED A lamp with integrated driver.

Mounting Mounts over 4" recessed outlet box.

Certification Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations







**Ordering Guide:** Choose from each category, using designated code to specify.

HL301 WM

MODEL **DIFFUSER** LIGHT SOURCE **FINISH EXTRAS** 

### Diffuser/Optics

CL - Clear glass FR - Frosted glass

### **Light Source**

MB25 A - 25W MAX. MED base (A19 lamp by others) MBL6A - 5.5W/30K 470 Lm OmniLED MBL9.8A - 9.8W/30K 800 Lm OmniLED GUL9.8A - 9.8W/27K 800 Lm GU24 OmniLED MBL10A JA8 - 10W/30K 800 Lm 90+ CRI OmniLED GUL11A - 11W/27K 1100 Lm GU24 OmniLED MBL11A - 11W/30K 1100 Lm OmniLED MBL13A JA8 - 13W/30K 1100 Lm 90+ CRI OmniLED

MB - 100W Max Incand A (by others)

WH - White

Finish

Standard

BL - Black

**DB** - Dura-Bronze

Upgraded\* RAL - Specify Color # **UPG** - Select Color from Luraline Pallette

Extras (Order Separately)

#### Premium\*

CCM - Custom Color CIC - Inner Color CTC - Clear Top Coat \* Subject to Surcharge

