



**Helos HL301XL PR** H: 35.25 W: 18 E: 32.50

**Description**

18" Disk, U-arm postlight (slips 4")

**Specifications**

<b>Housing</b>	Heavy-wall spun aluminum with cast fitter and extruded arm		
<b>Diffuser/Optics</b>	<ul style="list-style-type: none"> <li>• Clear prismatic glass cylinder</li> <li>• Clear tempered glass cylinder</li> <li>• Frosted Glass cylinder</li> </ul>		
<b>Light Source</b>	GUL	MBL	Medium Base
<b>Max Watts</b>	15	18	200
<b>Electrical</b>	<p><b>MB</b> - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.</p> <p><b>MBL</b> - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures.</p> <p><b>GUL</b> - Includes GU24 base 120V HPF Triac dimmable 25,000 Hr OmniLED A lamp with integrated driver.</p>		
<b>Mounting</b>	Slips 4" OD (PR Series) poles - order separately		
<b>Certification</b>	Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations		



**Ordering Guide:** Choose from each category, using designated code to specify.

HL301XL PR				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

**Diffuser/Optics**

- CL** - Clear glass
- CPR** - Clear prismatic glass
- FR** - Frosted glass

**Light Source**

- MB25 A** - 25W MAX. MED base (A19 lamp by others)
- MBL6A** - 5.5W/30K 470 Lm OmniLED
- MBL9.8A** - 9.8W/30K 800 Lm OmniLED
- GUL9.8A** - 9.8W/27K 800 Lm GU24 OmniLED
- GUL11A** - 11W/27K 1100 Lm GU24 OmniLED
- MBL11A** - 11W/30K 1100 Lm OmniLED
- MBL13A JA8** - 13W/30K 1100 Lm 90+ CRI OmniLED
- GUL15A** - 15W/27K 1600 Lm GU24 OmniLED
- MBL18A JA8** - 18W/30K 1600 Lm 90+ CRI OmniLED
- MB** - Maximum 200W A (by others)

**Finish**

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded\***
- RAL** - Specify Color #
- UPG** - Select Color from Luraline Palette
- Premium\***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- \* Subject to Surcharge

**Extras (Order Separately)**