



Helos HL301XL UWM H: 32 W: 18 E: 34 MC: 24

Description

18" Disk, U-arm

Specifications

Housing	Heavy-wall spun aluminum with cast fitter/canopy and extruded arm		
Diffuser/Optics	• Clear tempered glass cylinder • FR - Frosted Glass		
Light Source	GUL	MBL	Medium Base
Max Watts	15	18	200
Electrical	MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures. MBL - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures. GUL - Includes GU24 base 120V HPF Triac dimmable 25,000 Hr OmniLED A lamp with integrated driver.		
Mounting	Mounts over 4" recessed outlet box.		
Certification	Manufactured in accordance with U.L. standard 1598 - - Suitable for wet locations		



Ordering Guide: Choose from each category, using designated code to specify.

HL301XL UWM				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

CL - Clear glass
FR - Frosted Glass

Light Source

MB25 A - 25W MAX. MED base (A19 lamp by others)
GUL11A - 11W/27K 1100 Lm GU24 OmniLED
MBL11A - 11W/30K 1100 Lm OmniLED
MBL13A JA8 - 13W/30K 1100 Lm 90+ CRI OmniLED
GUL15A - 15W/27K 1600 Lm GU24 OmniLED
MBL15A - 15./30K 1600 Lm OmniLED
MBL18A JA8 - 18W/30K 1600 Lm 90+ CRI OmniLED
MB - Maximum 200W A (by others)

Finish

Standard
BL - Black
DB - Dura-Bronze
WH - White
Upgraded*
RAL - Specify Color #
UPG - Select Color from Luraline Palette
Premium*
CCM - Custom Color
CIC - Inner Color
CTC - Clear Top Coat
 * Subject to Surcharge

Extras (Order Separately)