



Helos HL301XL UWMX H: 32 W: 18 E: 34 MC: 24

Description

18" Disk, U-arm

Specifications

Housing	Heavy-wall spun aluminum with cast fitter/canopy and extruded arm
Diffuser/Optics	• Clear tempered glass cylinder • FR - Frosted Glass
Light Source	LED
Max Watts	14.69
Electrical	TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
Mounting	Mounts over 4" recessed outlet box.
Certification	Manufactured in accordance with U.L. standard 1598 - - Suitable for wet locations

Ordering Guide: Choose from each category, using designated code to specify.

HL301XL UWMX

MODEL

DIFFUSER

LIGHT SOURCE

FINISH

EXTRAS

Diffuser/Optics

CL - Clear glass
FR - Frosted Glass

Light Source

TL11 HO - 10.99W/40K 2470 Lm, 120V dimmable
TL11 - 11.3W/30K 2075 Lm, 120V dimmable
TL13 - 12.99W/30K 2352 Lm, 120V dimmable
TL14 HO - 14.28W/40K 3040 Lm, 120V dimmable
TL15 - 14.69W/30K 2626 Lm, 120V dimmable

Finish

Standard
BL - Black
DB - Dura-Bronze
WH - White
Upgraded*
RAL - Specify Color #
UPG - Select Color from
Luraline Palette
Premium*
CCM - Custom Color
CIC - Inner Color
CTC - Clear Top Coat
* Subject to Surcharge

Extras (Order Separately)

27K Non-Stock item -
consult factory for availability
35K Neutral White
DIM010 4-wire 0-10V
Dimming - 120-277V
(STANDARD on TL19 & higher)
SSP 10KV 120-277V
Supplemental Surge Protection