



Helos HL301X P2 H: 19.25 W: 10 E: 37

Description

10" Disk, Double U-arm postlight (slips 3")

Specifications

Housing	Heavy-wall spun aluminum with cast fitter and extruded arm
Diffuser/Optics	• Clear prismatic glass cylinder • Clear tempered glass cylinder • Frosted Glass cylinder
Electrical	TL/HO- L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
Mounting	Slips 3" OD (PX Series) poles - order seperately
Certification	Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations

Ordering Guide: Choose from each category, using designated code to specify.

HL301X P2				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

CL - Clear glass
CPR - Clear prismatic glass
FR - Frosted glass

Light Source

Finish

Standard
BL - Black
DB - Dura-Bronze
WH - White
Upgraded*
RAL - Specify Color #
UPG - Select Color from Luraline Palette
Premium*
CCM - Custom Color
CIC - Inner Color
CTC - Clear Top Coat
 * Subject to Surcharge

Extras (Order Separately)

27K Non-Stock item - consult factory for availability
2DIM010 LED 4-wire 0-10V Dimming - 120-277V
35K Neutral White
SSP 10KV 120-277V Supplemental Surge Protection