



**Helos HLD302XL PR** H: 30.50 W: 22 E: 34.50

### Description

22" Tapered shade, U-arm postlight (slips 4") Down light only!

### Specifications

|                 |                                                                                                                                                                                               |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Housing         | Spun aluminum shade with extruded arm and cast fitter                                                                                                                                         |
| Diffuser/Optics | <ul style="list-style-type: none"> <li>Lensed LED (no diffuser) for Dry locations only</li> <li>TurboLED Extra wide beam silicone optic</li> <li>TurboLED wide beam silicone optic</li> </ul> |
| Light Source    | LED                                                                                                                                                                                           |
| Max Watts       | 36.12                                                                                                                                                                                         |
| Electrical      | TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).                                     |
| Mounting        | Slips 4" OD (PR Series) poles - order separately                                                                                                                                              |
| Certification   | Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations                                                                                                               |



**Ordering Guide:** Choose from each category, using designated code to specify.

|             |          |              |        |        |
|-------------|----------|--------------|--------|--------|
| HLD302XL PR |          |              |        |        |
| MODEL       | DIFFUSER | LIGHT SOURCE | FINISH | EXTRAS |

#### Diffuser/Optics

- Lensed LED (no diffuser)
- LOW** - Wide beam optic
- LOX** - Extra wide beam optic

#### Light Source

- TL19 HO** - 19.3W/40K 3871 Lm, 120V dimmable
- TL20** - 19.9W/30K 3421 Lm, 0-10V dimmable
- TL23 HO** - 22.71W/40K 4410 Lm, 0-10V dimmable
- TL23** - 23.41W/30K 3931 Lm, 0-10V dimmable
- TL26 HO** - 26.16W/40K 4938 Lm, 0-10V dimmable
- TL27** - 26.98W/30K 4428 Lm, 0-10V dimmable
- TL30 HO** - 29.65W/40K 5455 Lm, 0-10V dimmable
- TL31** - 30.6W/30K 4913 Lm, 0-10V dimmable
- TL35 HO** - 34.95W/40K 6213 Lm, 0-10V dimmable
- TL36** - 36.12W/30K 5620 Lm, 0-10V dimmable

#### Finish

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded\***
- RAL** - Specify Color #
- UPG** - Select Color from Luraline Palette
- Premium\***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- \* Subject to Surcharge

#### Extras (Order Separately)

- 27K** Non-Stock item - consult factory for availability
- 35K** Neutral White
- DIM010** 4-wire 0-10V Dimming - 120-277V (STANDARD on TL19 & higher)
- SSP** 10KV 120-277V Supplemental Surge Protection