


Project:

Fixture Type:





RLM RD11 CORD

H: 9.75 W: 11.5 OAL: 46.5

### **Description**

11" Deep Bowl pendant with 36" Black 18-3 cord. (White cord supplied with white fixtures)

### Specifications

Housing Spun aluminum with stamped steel canopy

Diffuser/Optics • Bare lamp (no diffuser)

(for use in Dry locations)

· Clear tempered glass cylinder

• Frosted Glass cylinder

Light Source GUL MBL Medium Base

Max Watts 11 18 100

Electrical MB - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.

MBL - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures.

GUL - Includes GU24 base 120V HPF Triac dimmable 25,000 Hr OmniLED A lamp with integrated driver.

Mounting Mounts over 4" recessed outlet box.

Certification Manufactured in accordance with U.L. standard 1598 - Suitable for damp locations









Ordering Guide:	Choose from e	ach category,	using designated	code to specify.
-----------------	---------------	---------------	------------------	------------------

RD11 CORD

MODEL DIFFUSER LIGHT SOURCE FINISH EXTRAS

### Diffuser/Optics

Bare-lamp (no diffuser) **CL** - Clear glass **FR** - Frosted glass

#### **Light Source**

MB25 A - 25W MAX. MED base (A19 lamp by others)
MBL6A - 5.5W/30K 470 Lm OmniLED

MBL9.8A - 9.8W/30K 800 Lm OmniLED MBL10A JA8 - 10W/30K 800 Lm 90+ CRI OmniLED

**GUL11A** - 11W/27K 1100 Lm GU24 OmniLED

MBL11A - 11W/30K 1100 Lm OmniLED

MBL13A JA8 - 13W/30K 1100 Lm 90+ CRI OmniLED MBL18A JA8 - 18W/30K 1600 Lm 90+ CRI OmniLED

MB - 100W Max Incand A (by others)

## Finish

#### Standard

**BL** - Black **DB** - Dura-Bronze **WH** - White

Upgraded\*

RAL - Specify Color # UPG - Select Color from

# <u>Luraline Pallette</u> Premium\*

CCM - Custom Color CIC - Inner Color CTC - Clear Top Coat \* Subject to Surcharge

# Extras (Order Separately)

CG3 Cast aluminum guard (requires diffuser) SSP 120 4KV 120V MOV1 Surge Suppressor

