



**RLM RD14 P2** H: 25 W: 14 E: 41

## Description

14" Deep Bowl, Double U-arm postlight (slips 3")

## Specifications

|                        |  |         |             |
|------------------------|--|---------|-------------|
| <b>Housing</b>         | Spun aluminum shade with extruded arm and cast fitter  |         |             |
| <b>Diffuser/Optics</b> | <ul style="list-style-type: none"> <li>• Bare lamp (no diffuser) for Dry locations only</li> <li>• Clear glass</li> <li>• Frosted Glass cylinder</li> </ul>  |         |             |
| <b>Light Source</b>    | GUL  | MBL     | Medium Base |
| <b>Max Watts</b>       | 15 X 2   | 110 X 2 | 200 X 2     |
| <b>Electrical</b>      | <p><b>MB</b> - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.</p> <p><b>MBL</b> - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures.</p> <p><b>GUL</b> - Includes GU24 base 120V HPF Triac dimmable 25,000 Hr OmniLED A lamp with integrated driver.</p> |         |             |
| <b>Mounting</b>        | Slips 3" OD (PX Series) poles - order separately   |         |             |
| <b>Certification</b>   | Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations (with diffuser only)   |         |             |



**Ordering Guide:** Choose from each category, using designated code to specify.

|         |          |              |        |        |  |
|---------|----------|--------------|--------|--------|--|
| RD14 P2 |          |              |        |        |  |
| MODEL   | DIFFUSER | LIGHT SOURCE | FINISH | EXTRAS |  |

### Diffuser/Optics

- Bare-lamp (no diffuser)
- CL** - Clear glass
- FR** - Frosted glass

### Light Source

- 2MBL9.8A** - 19.6W/30K 1600 Lm OmniLED
- 2MBL10A JAS** - 20W/30K 1600 Lm 90+ CRI OmniLED
- 2GUL11A** - 22W/27K 2200 Lm GU24 OmniLED
- 2MBL15A** - 30W/30K 3200 Lm OmniLED
- 2GUL15A** - 30W/27K 3200 Lm GU24 OmniLED
- 2MB25A** - 2x 25W MAX. MED base (lamp by others)
- 2MBL11A** - 23W/30K 2280 Lm OmniLED
- MB** - Maximum 2x 200W A (by others)

### Finish

- Standard**
- BL** - Black
- DB** - Dura-Bronze
- WH** - White
- Upgraded\***
- RAL** - Specify Color #
- UPG** - Select Color from Luraline Palette
- Premium\***
- CCM** - Custom Color
- CIC** - Inner Color
- CTC** - Clear Top Coat
- \* Subject to Surcharge

### Extras (Order Separately)

- CG3** Cast aluminum guard (requires diffuser)