



RLM RS16 GNLX H: 16 W: 16 E: 24 MC: 3

Description

16" RLM, 14" L-arm

Specifications

Housing	Spun aluminum shade with extruded arm and cast canopy*
Diffuser/Optics	- FR - Frosted Glass - Lensed LED (no diffuser) for Dry locations only
Light Source	LED
Max Watts	9.62
Electrical	TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
Mounting	Mounts over 4" recessed outlet box.
Certification	Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations (with diffuser only)



Ordering Guide: Choose from each category, using designated code to specify.

RS16 GNLX				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

FR - Frosted glass
LOZ - Lensed LED (no diffuser)

Light Source

TL8 HO - 7.75W/40K 1886 Lm, 120V dimmable
TL8 - 7.96W/30K 1502 Lm, 120V dimmable
TL9 HO - 9.36W/40K 2179 Lm, 120V dimmable
TL10 - 9.62W/30K 1790 Lm, 120V dimmable

Finish

Standard
BL - Black
DB - Dura-Bronze
WH - White
Upgraded*
RAL - Specify Color #
UPG - Select Color from Luraline Palette
Premium*
CCM - Custom Color
CIC - Inner Color
CTC - Clear Top Coat
* Subject to Surcharge

Extras (Order Separately)

27K Non-Stock item - consult factory for availability
35K Neutral White
CG3 Cast aluminum guard (requires diffuser)
DIM010 4-wire 0-10V Dimming - 120-277V (STANDARD on TL19 & higher)
SSP 10KV 120-277V Supplemental Surge Protection