



**RLM RS16 STEM** H: 8 W: 16 OAL: 21.75

### Description

16" RLM pendant with 12" stem and 40° swivel canopy

### Specifications

|                 |                                                                                                                                                                                                                                                                                                                                                             |     |             |
|-----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|-------------|
| Housing         | Spun aluminum with extruded stem and stamped steel canopy                                                                                                                                                                                                                                                                                                   |     |             |
| Diffuser/Optics | <ul style="list-style-type: none"> <li>Bare lamp (no diffuser) for Dry locations only</li> <li>Clear tempered glass cylinder</li> <li>Frosted glass cylinder</li> </ul>                                                                                                                                                                                     |     |             |
| Light Source    | GUL                                                                                                                                                                                                                                                                                                                                                         | MBL | Medium Base |
| Max Watts       | 11                                                                                                                                                                                                                                                                                                                                                          | 13  | 100         |
| Electrical      | <b>MB</b> - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.<br><b>MBL</b> - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures.<br><b>GUL</b> - Includes GU24 base 120V HPF Triac dimmable 25,000 Hr OmniLED A lamp with integrated driver. |     |             |
| Mounting        | Mounts over 4" recessed outlet box.                                                                                                                                                                                                                                                                                                                         |     |             |
| Certification   | Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations (with diffuser only)                                                                                                                                                                                                                                                        |     |             |



**Ordering Guide:** Choose from each category, using designated code to specify.

|           |          |              |        |        |
|-----------|----------|--------------|--------|--------|
| RS16 STEM |          |              |        |        |
| MODEL     | DIFFUSER | LIGHT SOURCE | FINISH | EXTRAS |

#### Diffuser/Optics

Bare-lamp (no diffuser)  
**CL** - Clear glass  
**FR** - Frosted glass

#### Light Source

**MB25 A** - 25W MAX. MED base (A19 lamp by others)  
**MBL6A** - 5.5W/30K 470 Lm OmniLED  
**MBL9.8A** - 9.8W/30K 800 Lm OmniLED  
**MBL10A JA8** - 10W/30K 800 Lm 90+ CRI OmniLED  
**GUL11A** - 11W/27K 1100 Lm GU24 OmniLED  
**MBL11A** - 11W/30K 1100 Lm OmniLED  
**MBL13A JA8** - 13W/30K 1100 Lm 90+ CRI OmniLED  
**MB** - 100W Max Incand A (by others)

#### Finish

**Standard**  
**BL** - Black  
**DB** - Dura-Bronze  
**WH** - White  
**Upgraded\***  
**RAL** - Specify Color #  
**UPG** - Select Color from Luraline Palette  
**Premium\***  
**CCM** - Custom Color  
**CIC** - Inner Color  
**CTC** - Clear Top Coat  
 \* Subject to Surcharge

#### Extras (Order Separately)

**CG3** Cast aluminum guard (requires diffuser)  
**DWG16** 16" Wire Guard  
**SSP 120** 4KV 120V MOV1 Surge Suppressor