



Legacy Product SH14 CMX H: 9.50 W: 14

Description

MOQ of 24 pcs. required

Specifications

Housing	Stamped steel fitter and canopy
Diffuser/Optics	OP - Opal Glass
Light Source	LED
Max Watts	19.88
Electrical	TL/HO - L90 >55,000 Hrs. with TurboLED & TurboLED HO COB. 120-277V HPF Constant Current driver, LE-TE dimmable @120V and 0-10V dimming (model dependent).
Mounting	Mounts over 4" recessed outlet box.
Certification	Manufactured in accordance with U.L. standard 1598 - For dry locations only

Ordering Guide: Choose from each category, using designated code to specify.

SH14 CMX				
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS

Diffuser/Optics

OP - Opal Glass

Light Source

TL6 HO - 6.16W/40K 1588 Lm, 120V dimmable
TL6 - 6.32W/30K 1208 Lm, 120V dimmable
TL8 HO - 7.75W/40K 1886 Lm, 120V dimmable
TL8 - 7.96W/30K 1502 Lm, 120V dimmable
TL9 HO - 9.36W/40K 2179 Lm, 120V dimmable
TL10 - 9.62W/30K 1790 Lm, 120V dimmable
TL11 HO - 10.99W/40K 2470 Lm, 120V dimmable
TL11 - 11.3W/30K 2075 Lm, 120V dimmable
TL13 HO - 12.62W/40K 2756 Lm, 120V dimmable
TL14 HO - 14.28W/40K 3040 Lm, 120V dimmable
TL15 - 14.69W/30K 2626 Lm, 120V dimmable
TL16 HO - 15.94W/40K 3320 Lm, 120V dimmable
TL16 - 16.41W/30K 2895 Lm, 120V dimmable
TL19 HO - 19.3W/40K 3871 Lm, 120V dimmable
TL20 - 19.9W/30K 3421 Lm, 0-10V dimmable

Finish

Standard
BL - Black
DB - Dura-Bronze
WH - White
Upgraded*
RAL - Specify Color #
UPG - Select Color from [Luraline Palette](#)
Premium*
CCM - Custom Color
CIC - Inner Color
CTC - Clear Top Coat
 * Subject to Surcharge

Extras (Order Separately)

27K Non-Stock item - consult factory for availability
35K Neutral White
DIM010 4-wire 0-10V Dimming - 120-277V
SSP 10KV 120-277V Supplemental Surge Protection

NOTES: *Driver is housed in extended aluminum canopy (not shown)