



Decorative SP16 H: 16 W: 16

Description

Specifications

- Housing** Injection molded polycarbonate
- Diffuser/Optics** WACS - Seamless White Acrylic
- Light Source** MBL Medium Base
- Max Watts** 10 150
- Electrical**
 - MB** - Accepts Medium base 120V incandescent, CFL or LED lamps (by others) rated for use in fully enclosed fixtures.
 - MBL** - Includes Medium base 120V HPF Triac dimmable OmniLED A lamp rated for use in fully enclosed fixtures.
- Mounting** Slips 3" OD (P Series) poles - order separately
- Certification** Manufactured in accordance with U.L. standard 1598 - Suitable for wet locations



Ordering Guide: Choose from each category, using designated code to specify.

SP16					
MODEL	DIFFUSER	LIGHT SOURCE	FINISH	EXTRAS	

Diffuser/Optics

WACS - 1-piece White Acrylic (blow-molded)

Light Source

MB25 A - 25W MAX. MED base (A19 lamp by others)
MBL9.8A - 9.8W/30K 800 Lm OmniLED
MBL10A JAB - 10W/30K 800 Lm 90+ CRI OmniLED
MB - 150W Max Incand A (by others)

Finish

Standard
BL - Black
WH - White

Extras (Order Separately)